

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
4 November 2004 (04.11.2004)


PCT

(10) International Publication Number
WO 2004/094810 A1

- (51) International Patent Classification⁷: **F02M 19/03**
- (21) International Application Number: PCT/US2004/002186
- (22) International Filing Date: 27 January 2004 (27.01.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
PCT/US03/08635 19 March 2003 (19.03.2003) US
- (71) Applicant (for all designated States except US): **BETTER BURN, LLC** [—/US]; 1525 Perimeter Parkway, Suit 225, Huntsville, AL 35806 (US).
- (72) Inventor: **DELISLE, Gilles** [MX/US]; P.O.BOX 849, Mesilla Park, 88047 (MX).
- (74) Agent: **CLODFELTER, Mark**; 555 Sparkman Drive, Suite 1602D, Huntsville, AL 35806 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,

[Continued on next page]

(54) Title: ANTI-DETONATION FUEL DELIVERY SYSTEM



(57) Abstract: Apparatus sealably incorporating a fuel metering device and fuel processing device [200, 200a, 200b] for producing a stabilized fog of fuel droplets sized 50 microns and less that when mixed with combustion air burn completely, reduce or eliminate detonation (knock) in internal combustion engines and reduce fuel octane requirements. The apparatus [200, 200a, 200b] may include a carrier gas reservoir [216, 216a] closed to external carrier gasses. A heater [205] may be employed to flash into vapor a portion of the liquid fuel to develop a carrier gas. In embodiments for jet or turbine engines, bleed gas from the engine may be used to provide carrier gas through a fuel processor [254], or the fuel may be heated -by -heater [260] to flash some of the fuel into vapor to provide carrier gas through the fuel processor to produce the stabilized fog of fuel droplets.



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*